
SECTION 1 : IDENTIFICATION

PRODUCT NAME: Cuccio Colour Veneer- Color Gel- Brooklyn Never Sleeps Product Use: Nail Gel Polish Star Nail International, Inc./CUCCIO Chemical Family: UV Gels Manufacturer's Name : Address: 29120 Avenue Paine **Proprietary Mix** Valencia, CA 91355 CAS# N/A City, State, Zip :

Preparation Date: 04/01/2013

24 HR. EMERGENCY TELEPHONE: CHEMTEL 1-813-248-0573

SECTION 2: HAZARDS IDENTIFICATION



Potential Health Effects, Signs and Symptoms of Exposure:

Primary Route of Entry: No specific information is available for this product. Although, this product opposes only slight irritation concern

with all routes of entry. Eves: No specific information available. Contains materials that are essentially nonirritating, but contact may cause slight transient irritation. No specific information available. Contains materials that may cause moderate skin injury (reddening and Skin: swelling) and/or sensitization. Prolonged contact may cause blister formation (burns). Since irritation may not occur immediately, contact can go unnoticed. Ingestion No specific information available. Contains materials that may be practically nontoxic. Inhalation No specific information available. Low volatility makes vapor inhalation unlikely. Sub-Chronic Effects No specific information available. Limited tests showed no evidence of teratogenicity in animals. A lifetime skin painting study with mice showed no evidence of carcinogenicity.

NOTE: Refer to Section 11, Toxicological Information for Details

SECTION 3 : COMPOSITION/ INFORMATION ON INGREDIENTS

Chemical Identity	CAS#	EINECS#	INCI Name	Exposure OSHA TWA/STEL	Limits ACGIH TWA/STE	Carcinogen L IARC/NTP/	% OSHA
Polyurethane Acrylate Oligomer	Exempt	N/E	Di-Hema Trimethylhexyl Dicarbamate*	N/E	N/E	Not Listed	50-65
2-Hydroxyethyl Methacry	late 868-77-9	212-782-2	HEMA	N/E	N/E	Not Listed	5-10

Hydroxypropyl Methacry	ate 27813-02-1		Hydroxypropyl thacrylate	N/E	N/E	Not Listed	5-10
Polyethylene Glycol 400 Dimethacrylate	25852-47-5	N/E	PEG-9 Dimethacrylate	N/E	N/E	Not Listed	1-7
Isopropyl Alcohol	67-63-0	200-661-7	Isopropyl Alcohol	400ppm	400ppm	Not Listed	0-3
n-Butyl Acetate	123-86-4	204-658-1	Butyl Acetate	150ppm	150ppm	Not Listed	0-3
Ethyl Acetate	141-78-6	205-500-4	Ethyl Acetate	400ppm	400ppm	no/no/no	0-3
Hydroxycyclohexyl Pher Ketone	nyl 947-19-3	213-426-9	Hydroxycyclohexyl phenyl ketone	N/E	N/E	Not Listed	1 1-2
TPO	75980-60-8	278-355-8	Trimethylbenzoyl diphenylphosphine oxide	N/E	N/E	Not Listed	0-1

May Contain the following: Please see Section 16 for additional compounds

N/E - None Established N/R - Not Reviewed	N/DA - No Data Avail N/A - Not Applicable		n 16	
Polyurethane Acrylate Oligomer: 2-Hydroxyethyl Methacrylate: Hydroxypropyl Methacrylate: Polyethylene Glycol 400 Dimethacrylate:	Hazard Symbol: Xi Hazard Symbols – Xi Hazard Symbol: Xi Hazard Symbol – N/A	Risk Phrases: R36/37/38 Risk Phrases – R36/38, R43 Risk Phrases: R36/37/38, R43 Risk Phrases – R36/37/38	Safety Phrases: S14, S3/7, S62 Safety Phrases: S2, S26, S28 Safety Phrases: S26, S36/37 Safety Phrases – S26, S36/37	
Isopropyl Alcohol: n-Butyl Acetate: Ethyl Acetate: TPO: See Section 16 for Risk and Safety	Hazard Symbol – F, Xi Hazard Symbol: N/E Hazard Symbol – F, Xi Hazard Symbol: Phrase Key	Risk Phrases – R11, R36, R37 Risk Phrases: R10, R66, R67 Risk Phrases – R11, R36, R66, R Risk Phrases: R99	Safety Phrases – S2, S7, S16, S24/25, S26 Safety Phrases: S2, S25 867 Safety Phrases – S2, S16, S26, S33 Safety Phrases:	

SECTION 4 : FIRST AID MEASURES

First Aid for Eye: Flush with plenty of water for 15 minutes and retract eyelids often. Seek medical attention Immediately.

First Aid for Skin: Remove contaminated clothing and wash contact area with soap and water for 15 minutes.

First Aid for Inhalation: In case of exposure to a high concentration of vapor or mist, remove person to fresh air. If breathing has stopped, administer artificial respiration and seek medical attention.

First Aid for Ingestion: If appreciable quantities are swallowed, seek medical attention.

SECTION 5 : FIRE FIGHTING MEASURES

Flash Point	FlammableLimit	Auto Ignition Temperature
(°F/°C)	(vol%)	(vol%)
12 0 [°] F/49 ℃	No D <i>a</i> ta	No Data

Method:		
Extinguishing Media: Fire Fighting	Use carbon dioxide or dry chem ical for small fires; aqueous foarn or water for large fires.	
Instructions:	Remove all i gnition sources. Wear self-contain ed breathing apparatus and complete perso nal protective equi pment when entering confined areas where potential for exposure to vapors or products of combustion exists.	
Unusual Hazards:	High temperatures and fire conditions may cause rapid and uncontrolled polymerization which can result in Explosions and the violent rupture of storage vessels or containers. Avoid the use of a stream ofwater to control fires since frothing can occur.	

SECTION 6 : ACCIDENTAL RELEASE MEASURES

Spill or Release

Procedures: Spontaneous polymerization can occur. Eliminate ignition sources. Use eye and skin protection. Place leaking containers in a well ventilated area. Dike and recover large spills. Soak up small spills with inert solids (such as verniculite, clay) and sweep/shovel into disposal container. Wash spill area with strong detregent and water solution; rinse with water, but minimize water use during clean-up. Do not flush to sewer! US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. EU Regulations require the consultation of Directive 98/24/EC. Dispose and report per regulatory requirements if necessary. Please prevent washings from entering waterways.

SECTION 7 : HANDLING AND STORAGE

Handling: Avoid contact with skin and eyes. Avoid breathing vapor. Keep container closed when not in use. Avoid prolonged exposure to light. Remove all contaminated clothing, shoes, belts and other leather goods immediately. Incinerate leather goods (including shoes). Wash contaminated clothing thoroughly before reuse. Wash skin thoroughly with soap and water after handling. Solvents should not be used to clean skin because of increased penetration potential.

Most acrylic monomers have low viscosities, thus only needing room temperature conditions to facilitate proper
pouring techniques. However, viscous type gels such as these may require heating to facilitate proper pouring
techniques. To ensure that this happens, product may be heated to 60°C/140°F for not more than 24 hours. Do
NOT use localized heat sources such as band heaters to heat/melt product. Do NOT use steam. Hot boxes or hot
rooms are recommended for heating/melting material. The hot box and/or room should only be set to a
maximum temperature of 60°C/140°F. Do not overheat, this may compromise product effectiveness and should
be avoided. Refrain from multiple reheating of product, this will also diminishing the quality of the product.Storage:Product is extremely light sensitive. If exposed to natural light or UV light, material will cure very quickly. Store
in a cool, dry place, away from heat and all types of light. Store at temperatures below 100°F/38°C but above
the product's freezing point. If no freezing point is given, keep above 32°F/0°C at all times.Explosion Hazard:High temperatures and fire conditions may cause rapid and uncontrolled polymerization which can result in

explosion mazard. Fight competatures and the conditions may cause rapid and uncontrolled polymenzation when can result in explosions and the violent rupture of storage vessels or containers.

SECTION 8 : EXPOSURE CONTROLS/ PERSONAL PROTECTION

Engineering Controls: Local exhaust recommended to control exposure which may result from operations generating aerosols and hot operations generating vapors.

CUCCIO

MSDS

PRODUCT NAME: Cuccio Colour Veneer- Color Gel – Brooklyn Never Sleeps April 01, 2013 Personal Protective Equipment

General:

To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132), or European Standard EN166 be conducted before using this product. Provide eye wash stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit. Nitrile rubber is better than PVC.

Eye/ Face Protection: Wear chemical splash goggles.

Skin Protection: Wear impervious gloves (Neoprene).

Respiratory Protection: A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain limited circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by nuisance level organic vapor dust masks can be used, however the use of the respirator is limited. Follow OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

Appear	ance	Odor & Odor Th	reshhold	рН	Specific Gravity	Viscosity	% Volatile
	slight violet, s liquid	characteristic a	crylate odor	NA	(H2O=1): 1.15	(at 77°F/25°C) 1500-6000cP	By Volume: < 0.5
Delline		Octano / water Partitio ning					Solubility In
Boiling Point/Freezi ng Point	Decomposition Temperature	Co efficient Log Po/w	Vapor Pressure:	Vapor Density	Evaporation Rate	Ignition	Water (20°C)

Flash Point	FlammableLimit	Auto Ignition Temperature
(°F/°C)	(val%)	(vol%)
12 0 [°] F /49 ℃	No Data	No Data

SECTION 10: STABILITY AND REACTIVITY

Stability Normally Stable : Incompatibility (Materials to Avoid):

Polymerization initiators including peroxides, strong oxidizing agents, copper, copper alloys, carbon steel, iron, rust and strong bases.

Hazardous Decomposition Products:

Fumes produced when heated to decomposition may include: evolution of heat and increased pressure that could result in carbon monoxide, carbon dioxide.

Hazardous Polymerization:

May occur -- Uncontrolled polymerization may cause rapid evolution of heat and increased pressure that could result in violent rupture of sealed storage vessels or containers.

Conditions to Avoid:

Storage >100°F/38°C, exposure to light, loss of dissolved air, loss of polymerization inhibitor, contamination with incompatible materials.

SECTION 11: TOXICOLOGICAL INFORMATION

Acute Oral Toxicity	Acute Dermal Toxicity	Acute Inhalation Toxicity	Irritation – Skin	Irritation-Eye
No information available	No information available	No information available	No information available	No information available

Since this product contains a very bw concentration of active components, the primary toxicological information is derived from the oligomers. Further hazardous properties cannotbe excluded. The productshould be handled with care when dealing with chemicals

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicological Information

AcuteToxicity to fish	AcuteTo to Invertebra		Acute Toxicity to Algae	Bioconcentration	Toxicity to Sewage Bacteria	
NDA	N	/DA	NDA	NDA		N/DA
Jenskization		mata	gernerty		a cy	
N/DA	Ν		VDA	N/DA		

Chemical Fate Information

Biodegradability	NDA	
Chemical Oxygen Demand	NDA	

To the best of our knowledge, the ecotoxocological and chemical fate properties have not been thoroughly investigated. Do not allow to enter drinking water supplies, wastewater, or soil

SECTION 13: DISPOSAL CONSIDERATIONS

Non-contaminated, properly inhibited product is not a RCRA hazardous waste. It is the generators responsibility to determine

what is classified as a hazardous waste. Comply with all federal, state, and local regulations.

Dispose of diking materials and absorbent in compliance with State, Local, and Federal regulations. Residual vapors may explode on ignition; do not cut, drill, or weld on or near the container. Mix with compatible chemical which is less flammable and incinerate.

SECTION 14: TRANSPORTATION INFORMATION

CUCCIO MSDS PRODUCT NAME: Cuccio Colour Veneer- Color Gel – Brooklyn Never Sleeps April 01, 2013 DOT(49 CFR 172)

DUT (49 CFR 172)		
ProperShipping Name:	UN1993, Flammable liquids, n.o.s., (Isopropyl Alcohol, n- Acetate), 3, PGIII	Butyl
Identification Number:	UN1993	
Marine Pollutant	No	
Special Provisions:	T8,T31	
Emergency Response Guidebook (ERG) #.	128	
IATA (DGR):		
ProperShipping Name:	UN1993, Flammatile liquids, n.o.s., (Isopropyl Alcohol, n- Acetate), 3, PGIII	Butyl
Class or Division:	3	
UN or ID Number:	UN 1993	
Packaging Instructions:		
Emergency Response Guidance (ICAO)#:		
IMO (IMDG):		
ProperShipping Name:	UN1993, Flammable liquids, n.o.s., (Isopropyl Alcohol, n- Acetate), 3, PGIII	Butyl
Class or Division:	3.2	
UN orID Number:	UN 1993	
Special Provisions & Stowage/Segregation:	None	
Emergency Schedule (EmS)#:		
Other Information:	Flash point 49°C	

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

-		
	This product contains the following hazardous air pollutants (HAP), as defined by the U.S. Clean	
	AirAct	
	· NONE	
CleanAirAct: HAP/ODS	This product contains no ODSs	
	This product contains the following chemicals listed under the U.S.Clean WaterAct Prority Pollutant and Hazardous Substance List:	
Clean Water Act: Priority Pollutant	• Butyl Acetate, CAS# 123-86-4	
,,,,		
FDA: Food Packaging Status	This product has not been cleared by the FDA for use in food packaging and /or otherapplications as an indirect food additive.	
FDA. FUU Fackaying Status	an hairealiod addiive.	
	This productis considered to be a hazardous chemical under the OSHAHazard Communication	
	Standard. Its hazards are:	
	Immediate (acute) health hazard Delayed (chronic) health hazard	
Occupational Safety and Health Act	Reactive hazard	
	This product contains chemicals considered to be hazardous waste underRCRA(40 CFR	
	261):	
RCRA	· Ethyl Acetate CAS#141-78-6, RCR ACode U112	
	This product contains the following chemicals regulated under Sec. 302 as extremely	
	hazardous substances that carry a TPQ.	
SARATitle III: Section 302 (TPQ)	EthylAcetate CAS# 141-786, RQ(lbs.) 5000 EutylAcetate, CAS# 123-86-4, RQ(lbs): 5000	
SARA IIIE III. SECIOI 502 (TFQ)		
SARATite III: Section 302 (RQ)	This product contains no chemicals regulated under Section 304 as extremely hazardous chemical foremergency release notification ("CERCLA" List).	
	This productis considered haza roous under the OSHAHazard Communication Standard and is	
	regulated under Section 311-312 (40 CFR 370). Its hazards are:	
	Immediate (acute) health haza rd	
	· Delayed (chronic) health hazard	
SARATITE III: Section 311-312:	· Readive hazard	
	This product contains the following chemicals which are subject to the reporting	
	requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization	
SARATite III: Section 313:	Actof 1986 and 40 CFR Part 372: · Isopropyl Alcohol CAS# 67-63-0	
TSCASection 8(b): Inventory:	This product contains chemicals listed on the TSCAinventory or otherwise comples with TSCA pre-manufacture notification requirements.	
TSCASection (b): Inventory. TSCASignificant New Use Rule:	None of the chemical listed have a SNUR under TSCA.	
	[2-Hydroxyethyl methacrylate CAS# 868-77-9 is on the DSL List. W HMIS = n/da	1-
	sopropyl Alcohol CAS #67-63-0 is on the DSL list WHMIS = B2,D2B	
CDSL: Canadian Inventory	Butyl Acetate CAS #123-864 is on the DSL list. WHMIS=B2, D1B, D2B	
		1-1

Labeling according to EC directives – 1999/45/EC European Community:



Gel Polish:

- · HAZARD SYMBOLS: Xi: Irritant
- RISK PHRASES: R22: Harmful if swallowed, R36/38: Irritating to eyes and skin R43: May cause sensitization by skin contact.
- · SAFETY PHRASES: S18: Handle and open container with care, S24/25: avoid
- contact with skin and eyes, S36/37: Wear suitable protective clothing and gloves,
- S38: in case of insufficient ventilation, wear suitable respiratory equipment.

SECTION 16: ADDITIONAL REGULATORY INFORMATION

EU Classes and Risk /Safety Phrases for Referenced Ingredients (See Section 2):

Hazard Symbol:

Xi – I rritants

F – Flammable

Risk Phrases:

R10 – Flam mable; R11 – Highly Flam mable; R36 – Irritating to eyes; R43 - May cause sensitization byskin contact; R66 – Repeated exposuremay cause skin dryness and cracking; R67 – Vapors may cause drowsiness and dizziness, R36/37/38 - Irritating to eyes, respiratory system and skin; R36/38 - Irritating to eyes and skin

Safety Phrases:

S2 Keep out of the reach of children; S3'7 Keep containertightly closed in a cool place; ;S7 Keep containertightly closed;S16 Keep away from sources of ignition – No smoking; S2425 Avoid contact with skin and eyes; S26 In case of contact with eyes, rinse im mediately with plenty of waterand seek medical advice; S27 Take offi mmediately all contam inated clothing;S28 After contact with skin, wash immediately with plenty of water; S29 Do notempty into drains; S30 Never add water to this product; S33 Take precautionary measures against static discharges;S35 This material and its containermust be disposed of in a safe way;S36 Wear suitable protective clothing;S36/37 Wear suitable protective clothing and gloves;S62 Ifswallowed, do not induce vom iting: seek medical advice immediately and show this container or label

Hazard Rating System:

N	IFPA:	Health (2)	Flammabilty (2)	Reactivity (1)			
Η	HMIS: Health (2) Flammability (2) Reactivity (1)						

CUCCIO MSDS PRODUCT NAME: Cuccio Colour Veneer- Color Gel – Brooklyn Never Sleeps April 01, 2013 MAY CONTAIN THE FOLLOWING CHEMICALS:

Chemical Identity	CAS Numbers	EINECS #	INCI Name	Exposure OSHA TWA/STEL		Limits ACGIH TWA/STEL	Carcinogen IARC/NTP/OSHA	%
Titanium Dioxide	13463-67-7	236-675-5	Titanium Dioxide/CI77891	15 mg	g/m3	10mg/m3	3/no/no	0-2
Yellow Iron Oxide	51274-00-1	257-098-5	Iron Oxides/CI7	7492	N/E	N/E	Not Listed	0-2
Red Iron Oxide	1309-37-1	215-168-2	Iron Oxide/CI774	491	N/E*	N/E	Not Listed	0-2
D&C Red 7	5281-04-9	226-109-5	Red 7/CI15850	N	J/E	N/E	Not Listed	0-2
Synthetic Red Iron Oxide (maroon)	1309-37-1	N/E	Iron Oxides/CI774	191	N/E	N/E	Not Listed	0-2
D&C Orange No. 4	633-96-5	211-199-0	Orange 4/CI155	10	N/E	N/E	Not Listed	0-2
D&C Violet #2	81-48-1	201-353-5	Violet 2/CI6072:	5	N/E	N/E	Not Listed	0-2
Mica	12001-26-2	310-127-6	Mica	Ν	1/E	3mg/m3	Not Listed	0-2
FD&C Yellow #5	1934-21-0	217-699-5	Yellow 5/CI19	140	N/DA	N/D	A N/DA	- 0-2
D&C Red #6	5858-81-1	227-497-9	Red 6/CI15850)	N/DA	N/DA	N/DA	0-2
D&C Red #34	6417-83-0	229-142-3	Red 34/CI1588	30	N/DA	N/D/	A N/DA	0-2
Cosmetic Iron Blue	14038-43-8	237-875-5 Fer	5 Ferric rocyanide/CI7751	0	N/DA	N/DA	N/DA	0-2
D&C Yellow #10	8004-92-0	N/DA 10/	Yellow CI47005/E104		N/DA	N/DA	A N/DA	0-2
Ultramarine Blue	57455-37-5	N/DA	Ultramarines/CI	77007	/ N/D.	A N/I	DA N/DA	0-2
Manganese Violet	10101-66-3	233-257-4 V	Manganese iolet/CI77742		N/D.	A N/I	DA N/DA	0-2
FD&C Blue #1	3844-45-9	223-339-8	Blue 1/CI420)90	N	<u>́Е</u> №	J/E Not List	ed 0-2

D&C Black #2	1333-86-4	215-609-9 Blac	Carbon k/CI77266	3.5mg/m3 PAH	0.1 mg Groups 2B/A- 0-2 's/m3 4/Possible
					carbon black Select in presence of Carcinogen polycyclic aromatic hydrocarbon (PAHs)
N/E - None Established N/A-Not Applicable	N/DA–No Data A N/R - Not Review				

DISCLAIMER: This MSDS is intended to provide a brief summary of our knowledge and guidance regarding the use of this material. The information contained here has been compiled from sources considered by us to be dependable and is accurate to the best of the Company's knowledge. It is not meant to be an all-inclusive document on worldwide hazard communication regulations.

HAZA	RDOUS MATERIAL INDENTIFICATION HEALTH: FLAMMABILITY: REACTIVITY:	2 2 2					
	PERSONAL PROTECTION EQUIPM	ENT:	Glove	es and Safety Glasses			
NATIONAL FIRE PROTECTION ASSOCIATION (NF HEALTH: FLAMMABILITY: REACTIVITY: 1				PA) HAZARD IDENTIFICATION RATING: 2 2			
ABBREVIATIONS:							
NA NE	Not Applicable Not Established		ND	Not Determined			
pm mg gm kg Pa	Part per million Milligram Gram Kilogram Pascals		G L mol U p	Gallon Liter Mole Micro Pico			
LC TC BOD TLm	Lethal Concentration Toxic Concentration Biological Oxygen Demand Threshold Limit	TD	LD Toxic COD	Lethal Dose Dose Chemical Oxygen Demand			

CUCCIO

MSDS

PRODUCT NAME: Cuccio Colour Veneer- Color Gel – Brooklyn Never Sleeps April 01, 2013 DOC Dissolved Organic Carbon

H Hours D Days

- M Months
 - Y Years

- W Weeks
- ACGIH American Conference of Governmental Industrial Hygenist
- CPR Controlled Product's Regulation
- DSL Canadian Domestic Substances List
- NDSL Canadian Non-Domestic Substance List
- IARC International Agency for Research for Cancer
- NOEL No Observed Effect Level
- NOAEL No Observed Adverse Effect Level
- OSHA Occupational Safety and Health Administration
- PEL Permissible Exposure Limit
- TLV Threshold Limit Value