MSDS

PRODUCT NAME: Cuccio Colour Lacquer- Manhattan Mayhem **January 02, 2014**

This form is regarded to be in compliance with 29 CFR Part 1910.1200

SECTION 1 : IDENTIFICATION

PRODUCT NAME: **Cuccio Colour Lacquer- Manhattan Mayhem**
Product Use: Nail Enamel (CLEAR GLITTER SUSPENSION BASE)

Manufacturer's Name :	Star Nail International, Inc.	Chemical Family : Nitrocellulose
Address :	29120 Avenue Paine	Proprietary Mix
City, State, Zip :	Valencia, CA 91355	CAS# N/A

Preparation Date: 01/02/2014
24 HR. EMERGENCY TELEPHONE: CHEMTEL 1-813-248-0573

SECTION 2: COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS #	%	Hazard Symbol	Risk Phrases
Ethyl Acetate (**)	**141 - 78 - 6**	**20 - 35%**	**F, XI**	**R11, R36, R66, R67**
Butyl Acetate (**)	**123 - 86 - 4**	**15 - 30%**	**F**	**R10, R66, R67**
Nitrocellulose	**9004 - 70 - 0**	**5 - 20%**	**F**	**R11**
Ethyl Alcohol	**64 - 17 - 5**	**1 - 15%**	**F**	**R11**
Isopropyl Alcohol * (**)	**67 - 63 - 0**	**1 - 15%**	**F**	**R37, R11, R36, R67**
Triphenyl Phosphate	**115 - 86 - 6**	**0 - 10%**	**N**	**R50, R53**

*** Indicates toxic chemical (s) subject to the reporting requirements of Section 313 of Title III and of 40 CFR 372.**

** Indicates chemical subject to reporting requirements under CERCLA

SECTION 3 : HAZARDS IDENTIFICATION

Flammability : Highly Flammable
Inhalation : Prolonged inhalation may be harmful.
: Can cause drowsiness, headaches, nausea, vomiting and narcosis.
: May cause lung irritation.
Skin : Mild skin irritant, can cause non - allergic contact dermatitis.
Eyes : Eye irritant both liquid and vapor
Ingestion : Causes gastro - intestinal irritation, nausea, vomiting and diarrhea.
: Kidney damage

Risk Phrases/Hazard Symbols: NOTE: Definition of listed Risk Phrases and Hazard Symbols (Section 2.) can be found in Section 15.

SECTION 4 : FIRST AID MEASURES

Inhalation : Remove casualty to fresh air.
: Seek medical attention.
Skin : Wash off with propriety remover, wash affected area with soap and water.
Eyes : Irrigate with copious amounts of sterile water.
: Seek medical attention.
Ingestion : Do not induce vomiting. SEEK IMMEDIATE MEDICAL ATTENTION

The above information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.

SECTION 5 : FIRE FIGHTING MEASURES

MAGNITUDE APPLICABLE EXTINGUISHER TYPE
Small fire Carbon Dioxide, foam or dry chemical extinguishers.
Large fire Water or foam extinguishers, water fog.
note: - In all cases keep nearby containers cool by spraying with water.
Keep away from heat and sources of ignition

SECTION 6 : ACCIDENTAL RELEASE MEASURES

Personal Precautions Use suitable protective clothing/equipment.
Eliminate all sources of ignition. No Smoking.
Methods Of Cleaning Up Contain spillage with earth or sand.
Mop up small spill
Sweep up, use sand or earth to absorb spill for larger spillages
Environmental Precautions Do not allow to enter water courses or drains
Dispose in accordance with local regulation
Local authorities should be advised if significant spillages cannot be contained.

SECTION 7 : HANDLING AND STORAGE

Storage

Keep containers tightly closed, cool, dry, and away from sources of ignition, label containers
Eliminate possible point ignition sources, e.g. No smoking, Naked flames, static discharges.
Use flame proof electrical equipment.

Handling

No Smoking
Prevent static discharges.

Exposure by inhalation or skin contact should be minimized by good industrial hygiene.
Vapor is heavier than air, spreads along the ground.
Vapor can form an explosive mixture in air, prevalent in empty unclean vessels.
Use non - sparking utensils when handling this material.

SECTION 8 : EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Levels

Substance	OSHA - PEL	ACGIH
Ethyl Acetate (**)	400 ppm	400 ppm
Butyl Acetate (**)	150 ppm	150 ppm
Nitrocellulose	Not established	Not established
Ethyl Alcohol	1000 ppm	1000 ppm
Isopropyl Alcohol * (**)	400 ppm	200 ppm
Triphenyl Phosphate	<1	<1

Ventilation and extraction of appropriate design is necessary to meet the above levels.

The above information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.

Personal Protection
Chemical goggles should be worn.
Impervious gloves and overalls should also be worn.
An approved respirator should be worn if the maximum exposure levels above are surpassed.
HMIS RATING
Hazard Rating: (0=least, 1=slight, 2=moderate, 3=serious, 4=severe)
HEALTH: 2 FIRE: 3 REACTIVITY: 1 PP: G

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Liquid
Boiling/melting Point: Undefined
Flash Point: - 4° C or 24° F Method: TCC (Tag Closed Cup)
Upper/lower explosion limits: Undefined
Water Solubility: Insoluble
Vapor Density: Heavier than air
Specific Gravity (H2O=1): 0.98 - 1.10

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable under recommended storage conditions, affected by U.V., store away from direct sunlight.

Incompatible With: Strong oxidizing agents. Acids, Alkalines, and Peroxides

Hazardous Decomposition: Combustion of nitrocellulose may evolve nitrous oxid (poisonous) fumes.
CO, CO2, Nitrous Oxides, Smoke

Conditions to avoid: Flame, Electric spark, static and heat. Do not store @ Temperature Over 120°

Hazardous Polymerization: Will not occur.

SECTION 11: TOXICOLOGICAL INFORMATION

Toxicity: - LD 50 Rat: - Undefined

Organic solvents in the product may lead to removal of lipid soluble elements of the skin leading to non - allergic dermatitis upon repeated prolonged contact.
Vapor from solvents may cause: ill effects to the renal system; central nervous system problems; irritation to the respiratory tracts and other various mucosal membranes.

SECTION 12: ECOLOGICAL INFORMATION

Product should not be allowed to enter drains or water courses.
Used in large volumes, this product may incur the requirements of the Environmental Protection Act (pollution control/air).

SECTION 13: DISPOSAL CONSIDERATIONS

Dispose of product in accordance with local, county, state, and federal government Regulations.

The above information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.

SECTION 14: TRANSPORT INFORMATION

Proper Shipping Name : Paint
Technical Name : Nitrocellulose Lacquer
U.N. number : 1263
DOT Hazard Class : 3 (Flammable Liquid)
Packing Group : II
Flash Point : - 4°C or 24° F TCC (Tag Closed Cup)
ADR : Class 3; F1
Marine Pollutant : Yes (Triphenyl Phosphate)

SECTION 15: REGULATORY INFORMATION

UNITED STATES FEDERAL REGULATIONS:
SARA: See section 2 for reportable material
SARA TITLE III: See Section 2
CERCLA: See Section 2
TSCA: - Components in this product have been verified as being on the TSCA Inventory and have been classified in accordance with the hazard criteria of the CFR and all information required. -

STATE REGULATIONS:
Proposition 65: None

EU Risk Phrases :
R10 Flammable
R11 Highly Flammable
R20 Harmful by inhalation
R21 Harmful in contact with skin
R22 Harmful if swallowed
R36 Irritating to eyes
R37 Irritating to respiratory system
R38 Irritating to skin
R41 Risk of serious damage to eyes
R43 May cause sensitization by skin contact
R50 Very toxic to aquatic organisms
R53 May cause longterm adverse effects in the aquatic environment
R65 Harmful: may cause lung damage if swallowed
R66 Repeated exposure may cause skin dryness or cracking
R67 Vapors may cause drowsiness and dizziness.

EU Safety Phrases :
S16 Keep away from sources of ignition - No Smoking
S23 Do not breathe vapor.
S25 Avoid contact with eyes.
S29 Do not empty into drains.
S33 Take precautionary measures against.

Hazard Symbols :
Xn - Harmful
Xi - Irritant
F - Highly Flammable

NOTE: The appropriate Risk Phrases and Hazard Symbols pertaining to this product are listed Section 2.

The above information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.

SECTION 16: ADDITIONAL REGULATORY INFORMATION

DISCLAIMER: This MSDS is intended to provide a brief summary of our knowledge and guidance regarding the use of this material. The information contained here has been compiled from sources considered by us to be dependable and is accurate to the best of the Company's knowledge. It is not meant to be an all-inclusive document on worldwide hazard communication regulations.

This information is offered in good faith. Each user of this material needs to evaluate the conditions of use and design and the appropriate protective mechanisms to prevent employee exposure, property damage or release to the environment. Star Nail International assumes no responsibility for injury to the recipient or third persons, or for any damage to any property resulting from misuse of the product.

The above information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.

The above information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.